# **PCT**

# WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



# INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 4:	l	(11) International Publication Number: WO 87/02705
C12N 13/00, A01G 7/04 A01K 67/00	A1	(43) International Publication Date: 7 May 1987 (07.05.87)
(21) International Application Number: PCT/US8 (22) International Filing Date: 29 October 1986 (2 (31) Priority Application Number: (32) Priority Date: 29 October 1985 (2 (33) Priority Country:		Published  With international search report.
(33) Priority Country:	τ	JS
(71)(72) Applicant and Inventor: SWEENEY, Georam, Jr. [US/US]; 2382 Highway 138 SE, Con 30208 (US).	ge Wil yers, G	li- A
(74) Agents: FLOYD, John, P. et al.; Roberts & Flo 850, 1747 Pennsylvania Avenue, N.W., Was DC 20006 (US).	yd, Sui shingto	te n,
(81) Designated States: AT (European patent), AU, ropean patent), CH (European patent), DE (E patent), DK, FI, FR (European patent), GI pean patent), IT (European patent), JP, LU pean patent),	Europea R (Fur	in .
(54) Title: METHOD FOR ACCELERATING GR	OWTI	IDATES

(54) Title: METHOD FOR ACCELERATING GROWTH RATES

### (57) Abstract

Upon subjection to a low energy electrical field of varying and critical frequencies and low field strengths the growth rate of an organism disposed in a growth medium exhibits a significant increase over power-off controls.

BNSDOCID: <WO\_\_\_8702705A1\_I\_>

# FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

1					
AT AU BB BE BG BJ BR CF CG CH CM DE DK FI	Austria Australia Barbados Belgium Bulgaria Benin Brazil Central African Republic Congo Switzerland Cameroon Germany, Federal Republic of Denmark Finland	FR GA GB HU IT JP KP KR LI LK LW MC MG	France Gabon United Kingdom Hungary Italy Japan Democratic People's Republic of Korea Republic of Korea Liechtenstein Sri Lanka Luxembourg Monaco Madagascar !	ML MR MW NL NO SD SE SN SU TD TG US	Mali Mauritania Malawi Netherlands Norway Romania Sudan Sweden Senegal Soviet Union Chad Togo United States of America

# METHOD FOR ACCELERATING GROWTH RATES

# 1. Field of the Invention

This invention relates to a method for increasing the growth rate of biosystems. More particularly, this invention provides a method for accelerating the growth rates of organisms which involves the use of low energy electrical fields produced by a unique combination of applied low field strengths and extra-low electromagnetic frequencies.

## 2. Prior Art

- The effects of electrical fields on the stimulation of growth and regeneration in various biosystems have been studied. Mcelhaney et al., J. Biomech. 1:47 (1968) disclose the use of electrical fields to stimulate bone formation. The use of applied magnetic
- fields to accelerate growth in microorganisms is shown in U. S. Patent 3,871,961. Sewage decomposition promoting microorganisms are stated in U. S. Patent 3,336,220 to exhibit increased activity after an alternating electric current was passed through the sewage.
- MacKenzie in New Scientist, 28 January 1982, pp.
  217-220 reports on electrical fields which develop in
  connection with loss of limbs and which are implicated
  in the resultant regeneration phenomena. The effects
  of electrical fields on movement in an amoeba was
- 25 reported in Science, <u>187</u>:357 (1975).

Much of the work performed studying the effects of electrical fields on microorganisms has involved the study of mutagenesis and also sterilization, e.g., see Coate, W. B. et al. 1970, "Project Biological Effects Test Program Pilot Studies Final Report." Hazilton Laboratories, Inc., available from NTIS as AD717409, U. S. Patent 3,876,373 and Food Tehnol, 8:361 (1954).

30

10

It is an object of this invention to provide a unique and practical methodology utilizing low energy electrical fields to accelerate growth rates when applied to a living biosystem. It is a further object of this invention to increase such growth rates without producing mutants and without a measurable increase in the temperature of the biosystem. It is a still further object of this invention to provide an energy efficient, low cost and effective process for significantly reducing the growth cycle time of a biosystem.

### DESCRIPTION OF THE INVENTION

These and the other objects of this invention are accomplished by a process for accelerating the growth rate of a live organism which comprises disposing the organism in a suitable growth or nutrient medium and 15 subjecting the organism to an alternating electrical field at an electrical field strength and frequency combination which causes the growth rate of the organism to increase over the growth rate of the organism when not subjected to the alternating electrical field. 20 The desired increase in growth rate is independent of current density and is exhibited at varying frequencies and electrical field strengths. However, as far as has been tested there appear to exist certain critical frequencies, or regions of frequencies, at which acceler-25 ated growth occurs and outside of which there is minimal or no effect. Also at such effective frequencies there exists a threshold electrical field strength below which there is no effect. It has also been found that, within the ranges of effective frequencies and 30 field strengths, the resultant electrical field is a low energy field which does not produce mutants of the organism; nor is there a measurable increase in the temperature of the biosystem. Furthermore, in the preferred ranges of effective frequencies and strengths there is no electrolysis of the growth medium.

35

found that the effective frequencies and voltages are independent of current density. However, there is a practical limitation on current density in that one would not employ currents that adversely affect the biosystem. Tests have been conducted at less than 0.1 mA (milliamp) and it is believed that absolutely no current is required to effectively increase growth rates, so long as effective field strengths and frequencies are utilized in carrying out the invention.

## 10 Definition of Terms

"Growth Rate (rate)" - This is obtained by taking the Klett units over time and calculating the doubling time for the culture. This is done by plotting the Klett unit number of each reading on the log scale of a semilog graph (wherein the y axis is the semi-log scale and the x axis is time). The slope (m) of the curve is then calculated using the following formula:

$$m = \frac{E_{XY} - E_{X}E_{Y}}{N}$$

$$E_{X}^{2} - \frac{(E_{X})^{2}}{N}$$

wherein m is the slope, x is time, y is the semi-log, and N is the number of individual Klett readings.

"Klett units" - a unit of measurement of optical density employing a Klett-Summerson photoelectric colorimeter.

"LeeGs value (L)" is obtained by dividing the growth
rate of the test sample by the growth rate of the
control sample thus

$$L = \frac{G \text{ test}}{G \text{ cont}}$$

"Correlation (coor)" is calculated in accordance with following mathematical sequence:

$$corr = R = \frac{Ms_X}{s_Y}$$

wherein s is the standard deviation of the x and y axes of the semi-log graph referred to in the definition of growth rate.

"Dev" is an abbreviation for the standard deviation between the control groups calculated in the following manner:

wherein x is the value of the growth rate of each control group and n is the number of control groups.

"L-broth" - a growth medium consisting of 0.8% NaCl, 0.8% glucose and 0.7% bacto-tryptone, all percentages being weight to volume of tap water.

"Biosystem" - a system comprised of the organism disposed in a medium suitable for its normal growth.

"Hz" - abbreviation for hertz, a unit synonomous for cycle per second.

20 "KHz" - 1 kilohertz or 1000 hertz.

"ATCC" - American Type Culture Collection a depository for microorganisms located in Rockville, Maryland.

## Example 1

An overnight exponential culture of prototropic E.

coli K-12 (Yale University depository number CGSC No. 4401) growing at 37°C, in L-broth was diluted with thermally equilibrated and sterilized L-broth to a density of 1 x  $10^6$  cells per milliliter. Portions of this culture were then randomly placed into 10 ml. glass test tubes made of the type glass specified for the colorimeter employed. Each test tube contained two platinum electrodes, spaced 4 centimeters apart, wired in series to a variable frequency generator and in 10 parallel to an oscilliscope, and equipped with means for oxygen input to the growth medium. The tubes containing the fractionated culture medium were maintained at constant temperature in a thermostatically controlled water bath and each subjected to an electromotive (EmF) field. Temperature was monitored with a 15 glass/mercury thermometer. Each tube was isolated from the field of the other tubes by brass screening. This brass screening was grounded to totally eliminate any electrical transfer from one tube to the other. The 20 culture densities of each test tube were tested with a Klett-Summerson photoelectric colorimeter by measuring, at 20-30 minute intervals over a 3 hour period, increasing optical absorbences at 660 nanometers. Controls were also run using cells that were inac-25 tivated by subjecting them momentarily to 60°C and quick cooling to 37°C. Each set of controls consisted of three test tubes which were measured at 10, 100 and 1000 hertz to establish the background of optical absorbence effects due to the electroplating of cells and growth medium components onto the electrodes and 30 also to ascertain any electrolytic effects that might be present. The EmF fields were produced by the variable frequency generator and monitored via the oscilliscope. The low energy fields were applied by

passage of alternating current through the growth medium between the platinum electrodes.

The results obtained with E. coli, following the above procedure are set forth in the following tables.

5 Table 1 At 37°C, 1KHz, 10V.cm

time	0	20	40	60	80	rate	coor
con	37 37	39 41	42 45	48 58	52 53	0.37	
			1.27	•			

\*\*\*\*\*\*

Table 2 At 34°C, 1KHz, 18V/cm

	time	0	30	60	rate	coor
15	conl	66	68	72	0.12	0.98
	con2	50	52	55	0.14	0.99
	expl	49	53	58	0.24	1.00
	exp2	93	98	105	0.17	1.00

cont avg. = 0.13, dev = 0.01L1 - 1.85, L2 - 1.31

\*\*\*\*\*

20 Table 3

At 37°C, 10KHz; 5V/cm

	time	0	30	60	rate	coor
25	con1	65	76	88	0.44	1.00
	con2	65	78	89	0.46	1.00
	exp1	71	84	99	0.48	1.00
	exp2	66	81	98	0.57	1.00

cont avg. = 0.45, dev = 0.01L1 - 1.07, L2 - 1.27

\*\*\*\*\*\*

· Table 4

At 37°C, power off

	time	60	90	rate	coor
5	conl	88	107	0.56	1.00
	con2	89	108	0.56	1.00
	expl	99	112	0.36	1.00
	exp2	98	112	0.39	1.00

cont avg. = 0.56, dev = 0.00L1 - 0.64, L2 - 0.70

\*\*\*\*\*\*

10

Table 5

At 37°C, 1KHz, 5V/cm

	time	120	150	rate	coor
15	conl	141	154	0.25	1.00
	con2	130	148	0.37	1.00
	expl	137	151	0.28	1.00
	exp2	135	151	0.32	1.00

cont avg. = 0.31, dev = 0.08L1 - 0.90, L2 - 1.03

\*\*\*\*\*\*

Table 6

20

At 37°C, 1KHz, 5V/cm

	time	0	10	95	110	rate	coor
25	conl	62	64	91	94	0.34	1.00
	con2	58	61	89	95	0.42	1.00
	expl	77	82	123	117	0.79	0.98
	exp2	64	68	94	95	0.65	0.99

cont avg. = 0.38, dev = 0.06 L1 - 2.08, L2 - 1.71

\*\*\*\*\*

Table 7
At 36°C, 100Hz, 5V/cm

	time	0	30	60	rate	coor
5	conl	133	138	153	0.20	0.96
	con2	140	144	152	0.12	0.98
	expl	135	139	152	0.17	0.96
	exp2	144	149	159	0.14	0.98

cont avg. = 0.16, dev = 0.06L1 - 1.06, L2 - 0.88

\*\*\*\*\*\*

10

Table 8

At 37°C, 1KHz, 10V/cm

	time	0	30	60	90	120	rate	coor
15	conl	120	135	153	174	200	0.36	1.00
	con2	132	141	158	179	200	0.30	1.00
	expl	128	141	164	185	200	0.34	1.00
	exp2	125	137	160	180	200	0.35	1.00

cont avg. = 0.33, dev = 0.04Ll - 1.03, L2 - 1.06

\*\*\*\*\*\*

Table 9

20

At 34°C, 500Hz, 5V/cm

	time.	0	30	60	rate	coor
	conl	132	144	158	0.26	1.00
	con 2	. 129	145	155	0.27	0.99
	expl	121	136 ·	146 .	0.27	0.99
25	exp2	112	120	133	0.25	0.99

cont avg. = 0.27, dev = 0.01L1 = 1.00, L2 = 0.93

\*\*\*\*\*\*

Table 10
At 40°C, 5KHz, 5V/cm

	time	00	30	90	rate	coor
5	conl	108	119	142	0.26	1.00
	con2	107	113	139	0.25	0.99
	expl	107	121	140	0.26	0.99
	exp2	113	126	142	0.22	0.99

cont avg. = 0.26, dev = 0.01L1 = 1.00, L2 = 0.85

\*\*\*\*\*\*

10

Table 11

At 37°C, 1KHz, 8V/cm

	time	0	30	60	90	120	rate	coor
15	conl	98	103	106	115	122	0.16	0.99
	con2	103	105	109	116	125	0.14	0.97
	expl	95	100	109	120	122	0.20	0.98
	exp2	95	102	115	118	120	0.18	0.95

cont avg. = 0.15, dev = 0.01L1 = 1.33, L2 = 1.20

\*\*\*\*\*\*

Table 12

20

At 37°C, 100Hz, 5V/cm

time	0	<u> 70</u>	90	rate	coor
conl	107	127	129	0.19	0.99
con2	93	111	115	0.21	1.00
expt	95	116	113	0.19	0.94

cont avg. = 0.20, dev = 0.01, L = 0.95

\*\*\*\*\*\*

Table 13
At 37°C, 1KHz, 3V/cm

	time	. 0	70	90	rate	coor
5	conl	107	127	129	0.19	0.99
	con2	93	111	115	0.21	1.00
	expt	84	100	107	0.23	1.00

cont avg. = 0.20, dev = 0.01, L = 1.15

\*\*\*\*\*\*\*

Table 14

At 37°C, 10KHz, 5V/cm

10	time	0	30 ·	60	rate	coor
	conl	33	34	37	0.16	0.96
	con2 expt	33 33	34 34	37 39	0.16 0.23	0.96 0.94

cont avg. = 0.16, dev = 0.00, L = 1.44

\*\*\*\*\*\*

Table 15

15 At 37°C, 1KHz, 4V/cm

time	0	. 30	60	rate	coor
conl	33	34	37	0.16	0.96
con2	33	34	37	0.16	0.96
expt	38	42	48	0.33	1.00

20 cont avg. = 0.16, dev = 0.00, L = 2.06

\*\*\*\*\*\*

10

Table 16
At 35°C, lKHZ, 4V/cm

	time	0	30	60	90	120	rate	coor
5	conl	36	41	44	48	54	0.28	1.00
	con2	39	44	50	62	79	0.48	0.99
	expt	39	45	59	78	103	0.67	0.99

cont avg. = 0.38, dev = 0.14, L = 1.76

\*\*\*\*\*\*

Table 17

At 34°C, 1KHz, 2V/cm

10	time	0	30	60	90	120	rate	coor
	conl	36	41	44	48	54	0.28	1.00
	con2	39	44	50	62	79	0.48	0.99
	expt	44	47	53	60	65	0.29	1.00

cont avg. = 0.38, dev = 0.14, L = 0.76

\*\*\*\*\*

15

Table 18

At 37°C, .0Hz, 4V/cm

	time	0	30	60	85	rate	coor
20	conl	42 .	43	44	42	0.01	0.18
	con2	37	38	39	34	-0.07	-0.46
	expt	35	48	55	70	0.70	0.99

\*\*\*\*\*\*\*\*

## Table 19

## 1KHz, 1V, 0.4% NaCl

	time	00	46	61	75 ·	rate	coor
25	cont expt	23 23	31 31	34 36	36 42	0.49	0.98

(Power was inadvertently on on the control at lKHz., 0.5V until the time of the 46 minute reading, therefore the valid reading would start at that time. Starting

from 46 minutes the results turn out that the growth rate of the control turns out to be 0.45 gen/hr with a correlation of 0.99 and the rate of the experimental is 0.90 gen/hr with 1.00 correlation. This gives L=2.00 which corresponds with previous data.)

\*\*\*\*\*

### Table 20

Testing of 0.4 & 0.2% NaCl to show that the effect is not due to current.

1KHz., 1V

				TVL	12., 10				
10	time	0	30	60	70	80	90	rate	coor
	0.4%	20.0 9.0	22.0 10.0	25.0 10.0	27.5 11.5	29.5 12.5	32.0 14.0	0.43 0.36	0.98 0.91
				pow	er off			-	
	time	0	<del></del>	30		60	r	ate	coor
15	0.4% 0.2%	32.0 14.0		35.5 L5.0		9.5 7.0	_	. 29 . 28	0.90
				1KH	z., lv				
	time	0	3	LO	20	3(	0	rate	coor
20	0.4%	39.5 17.0	42. 21.		47.5 22.5	49.0 24.5	_	0.66	0.98
	0.4%	rate av	7 <b>q.</b> = 0	.54.	div =	0.16. 1	r. = 7 1	36	

That mutagenesis was not implicated in the acceleration of growth rates for <u>E. coli</u> was demonstrated by presence of carbon dioxide evolution when a culture medium from Example 1 was added to a test tube containing lactose and mineral salts at the temperature of 43°c (Eijkmann-Durham Test for contaminants).

0.2% rate avg. = 0.72, div, div = 0.50, L = 2.57

BNSDOCID WO RTOTAGE IS

## Example 2

The procedure of Example 1 was followed except that the microorganism was  $\underline{Bacillus}$   $\underline{subtilus}$  (ATCC 6051). The following results were obtained:

5 power off (control) temp. = 22c

<u>time</u>	0	30	60	rate	coor
A	0.126	0.132	0.145	0.200	0.980
B	0.028	0.033	0.036	0.370	0.980

## power lKHz, lV/cm

10	time	0	30	60	90	rate	coor
	A B				0.206 0.064	0.336 0.553	1.000

 $A_L = 1.68$ ;  $B_L = 1.50 L = 1.59$ 

### Example 3

The procedure of Example 1 was employed except that 2% Bacto yeast extract (Fleichman's fresh active yeast) was employed in place of <u>E. coli</u> and was grown at 25°C in an aqueous solution of 0.3% Bacto-Tryptone and 4.0% glucose (percentages are weight to volume water). The following results were obtained:

### power off (control)

	time	0	60	1	.20	rate	coor
٠	1 -	67 99	69 100		5 .05	0.05 0.04	1.00
25			lkh	z., lV/c	em.		
	time	00	60	120	180	rate	coor
	1 2	71.5 105	75 110	81 <sub>.</sub> 113	83 118	0.08 0.05	0.98

power off (control)

	time	0		50	rate	coor
	ch-l ch-2	83 118		35 20	0.03	1.00
5			power 100 H	Hz., lV/cm.		
	time	0	60	100	rate	coor
	1 2	85 120	87.5 123	. 89 124	0.04 0.03	1.00
10		cont	<pre>ch-l avg = ch-2 avg = ch-l lKHz.</pre>	0.03, dev	= 0.01	
		rate	ch-2 lKHz. L lKHz. a	= 0.05, L =	= 1.67	
15			ch-1 100 Hz ch-2 100 Hz	= 0.04, 1		

### Example 4

This example demonstrates the efficacy of the process of the invention in accelerating plant growth rates.

- Glass or plastic containers containing soil and bean seeds (Bountiful Green Bush variety of Pinto) were configured for generation of low energy electrical fields in the following four modes:
- parallel brass screens above and below the soil
   between which the beans are positioned without touching the screens
  - 2. one brass screen parallel to the side of the container with the seeds spaced apart therefrom with intervening soil in between the seeds and the screen
- 30 3. parallel wires in the horizontal plane of the bean seeds and spaced apart therefrom

4. one brass screen at the bottom of the container below the bean seeds.

Each container had from 4-8 bean seeds planted therein. All wires and screens were connected in series to an alternating current generator capable of producing multiple functions (e.g., sine or square waves). For each planted container connected to the generator there was a power-off control container of the same configuration. All other conditions were the same for

controls and test groups. To each test container were applied 22 volts (approximately 2.5 volts/cm.) at 1 KHz over a period of one week. At the end of the test period the test groups averaged about 8.5 inches in height, whereas the controls had just commenced to ger-

minate. The test group had significantly higher germination success than the controls. At comparable stages of development the test group was more vigorous in appearance than the controls and hence appeared to exhibit an increase in developmental success.

## 20 Example 5

Into a glass container was added a brass screen upon which was placed fruit fly medium containing freshly laid eggs. On top of the medium was placed another screen which along with the screen on the bottom of the container, was connected in series with a variable frequency generator. To the test sample was applied a field of lKHz, 22V (about 2.5 V/cm.); the control was a power off sample. The flies (Drosophila melanogaster) were then observed to eclosure (reaching of adulthood), and observed to show an earlier eclosure in the test sample than the control. The test sample also exhibited a greater hatching and eclosure success

and also was more vigorous (i.e., observably significantly more active than the control.)

The foregoing examples demonstrate that 1000 Hz and 10,000 Hz are highly preferred effective frequencies for growth rate acceleration with widely differing species of organisms at field strengths, which can be expressed in terms of volts per centimeter, ranging upwards of from about 1 volt per centimeter to about 22 volts per centimeter at the expressed frequencies.

- However, positive growth rate acceleration can be achieved at selected frequencies ranging upwards from 10 Hz to about one megahertz (MH<sub>Z</sub>), the only practical limitation being that point at which mutagenesis occurs. A wide range of field strengths can be
- employed at each selected effective frequency with a concomitant threshold field strength below which no effect occurs. Again practicality dictates that the upper limit for such field strengths is that point at which a measurable temperature increase occurs in the
- 20 biosystem. Selection of these critical frequencies and field strengths can routinely be accomplished by performing a simple series of tests as follows:

Set up electrodes so that electrical
field is applied across the biosystem, to
which electrodes are applied selected
frequencies at a set minimal field
strength of lV/cm. Upon discovery of an
effective frequency for growth rate
increase, various field strengths are
applied at the set effective frequency to
determine the effective field strength

RNSTACIO «WO A70270541 I

10

range. With microorganisms it is recommended that the system be designed essentially as described in Example 1. With plant or animal species any one of the systems described in Example 4 can be utilized. If no effective frequency is found at 1 volt/cm., repeat procedure at 5 volts/cm. and at 5 volt increments thereafter until an effective growth rate increasing frequency is found or until a measureable temperature increase occurs in the biosystem using a standard glass mercury thermometer.

Increase of growth rates while improving developmental success and vitality of some organisms in accordance with this invention has important commercial implications for industrial fermentation, as well as, agricultural and pharmaceutical production industries.

Improved yields and increased production capacities are direct advantages. Shorter organism growth cycle could open new vistas in diagnostic medicine as well as other areas of medicine such as bone marrow regeneration, organ regeneration, tissue revitilization and the like.

#### What is claimed is:

- l. A method of increasing the growth rate of a living organism which comprises disposing the organism in a growth medium and subjecting the organism to a low energy electrical field produced by a combined field strength and frequency effective for increasing the growth rate of said organism.
- The method of claim 1 wherein said field strength is above about 1 volt per centimeter and said
   frequency is selected from about 10 to about 10<sup>6</sup> Hz.
  - 3. The method of claim 1 wherein said organism is a microorganism or plant or animal.
- 4. The method of claim 3 wherein said voltage is above about 1 volt per centimeter and said frequency is selected from about 1000 Hz and about 10,000 Hz and the resulting electrical field does not increase the temperature of the medium.
- 5. The method of claim 3 wherein said voltage is selected from above about 1 volt per centimeter to about 22 volts per centimeter and said frequency is about 1000 Hz or about 10,000 Hz.

# INTERNATIONAL SEARCH REPORT

International Application NoPCT/US 86/02271

I. CLASSIFICAT	TION OF SUBJECT MATTER (if several c	lassification symbols apply Indicate all 1	US 86/02271
According to Inter	rnational Patent Glassification of CT2N 13700; A01G7/04;	National Classification and IPC	···
U.S. C1:	435/173; 426/2; 47/1	AUIK 6//UU	
II. FIELDS SEAF		, 119/1	
II. FIELDS SEAF			
Classification Syste		umentation Searched 4	
	1	Classification Symbols	
U.S.	435/173,243;426/2;	47/1.3;119/1	
	Documentation Searched oth to the Extent that such Docume	ner than Minimum Documentation ents are included in the Fields Searched 6	
	CONSIDERED TO BE RELEVANT 14		
Category • Ci	tation of Document, 16 with indication, where a	appropriate, of the relevant passages 17	Relevant to Claim No. 18
-	US, A, 3,336,220 (NEIDL) 15 August 1967, See col. 2, lines 15-20, col. 3, lines 5-20 and 45-50, and col. 6, lines 27-30.		
	EP, A 0041373 (WORTH) 1981, see entire docu	$\frac{1,3}{2,4,5}$	
-	SU, A, 721 480, 18 Ma see translated abstra	$\frac{1}{2}, \frac{3}{4}, \frac{5}{5}$	
X Y	SU, A, 842105, 30 June see translated abstrac	e 1981, ct.	1,3 2,4,5
		•	
"A" document dafi considered to "E" earlier documen filing date "L" document whi which is cited citation or oth "O" document rele other means "P" document publiater than the	es of cited documents; 15 ining the general state of the art which is not be of particular relevance ent but published on or after the international ch may throw doubts on priority claim(s) or to establish the publication date of another er special reason (as specified) rring to an oral disclosure, use, exhibition or lished prior to the international filing date but priority date claimed	"T" later document published after the or priority date and not in conflict cited to understand the principle invention.  "X" document of particular relevance cannot be considered novel or involve an inventive step.  "Y" document of particular relevance cannot be considered to involve a document is combined with one cannot be considered to involve a document is combined with one of ments, such combination being of in the art.  "4" document member of the same particular relevance cannot be considered to involve a document is combined with one of ments, such combination being of the same particular relevance.	t with the application but or theory underlying the e; the claimed invention cannot be considered to e; the claimed invention inventive step when the or more other such docu- poious to a person skilled
V. CERTIFICATIO			
January 19	ompletion of the International Search *	Date of Mailing of this International Sea	
nternational Searchir		Signature of Authorized Office) 20	<u>-</u>
SA/US		David M. Naff	
n PCT/ISA/210 (seco	ond sheet) (October 1981)	, David M. Nati	<del></del>

FURTH	ER INFORMATION CONTINUED FROM THE SECOND SHEET	PCT/US 86/02271
	The Second Sheet	
i		<u> </u>
x	DE A 2841455 (CROPPY) 10 - 10	ļ
$\frac{\mathbf{X}}{\mathbf{Y}}$	DE, A, 2841455 (GERTH) 10 April	1,3
-	1980, see translated abstract.	$\frac{1,3}{2,4,5}$
A	SII A 745020 17 7010 1000	
''	SU, A, 745939, 17 July 1980, see translated abstract.	
ĺ	didistated abstract.	
A	TIC 3 2 400300	
l ''	US, A, 2,492128 (SHROPSHIRE), 20	
	December 1949, see entire document.	<i>P</i> 15
		ł
		1
V. OB	SERVATIONS WHERE CERTAIN CLAIMS WERE FOUND UNSEARCHABLE 10	
	national search report has not been established in respect of certain claims under Article 1	7/0\ / \ / \
1. Clair	n numbers, because they relate to subject matter 12 not required to be searched b	/(2) (a) for the following reasons:
	be searched b	y this Authority, namely:
	•	
	•	
. —		
2. Clain	n numbers, because they relate to parts of the international application that do not	comply with the prescribed require-
ment	s to such an extent that no meaningful international sparch can be carried out <sup>13</sup> , specifica	illy:
		•
•		
VI. OBS	SERVATIONS WHERE UNITY OF INVENTION IS LACKING 11	
This Interna	ational Searching Authority found multiple investigations	
	ational Searching Authority found multiple inventions in this international application as fo	llows:
	•	
	·	
1 🗀 Anau	enguland address.	
of the	required additional search fees were timely paid by the applicant, this international search international application.	report covers all searchable claims
those	ly some of the required additional search fees were timely paid by the applicant, this inter- claims of the International application for which fees were paid, specifically claims:	national search report covers only
	talins:	
	·	•
3. No req	ulred additional search fees were timely early but the annual and	
the inv	ulred additional search fees were timely paid by the applicant. Consequently, this internall ention first mentioned in the claims; it is covered by claim numbers:	lonal search report is restricted to
	The service of claim homogra:	
	·	
As all	searchable claims could be searched without off a trust of a searched	
	searchableclaims could be searched without effort juștifying an additional fee, the Interna Jayment of any additional fee.	tional Searching Authority did not
Remark on P		
☐ The ad	ditional search fees were accompanied by applicant's protest.	ı
No pro	test accompanied the payment of additional search fees.	ļ

PCT/US 86/02271				
Category •	Citation of Document, 16 with indication, where appropriate, of the relevant passages 13	Relevant to Claim No		
A :	US, A, 3,871,961 (GIANESSI), 18 March 1975, see entire document.	l .		
A :	US, A, 4,487,834 (BRIGHTON), 11 December 1984, see entire document.			
	; ! :			
· :	•			
	•			

Form PCT ISA-210 (extra sheet) (October 1981)

THIS PACK BLANK USOTO,